

# **TA-20 Flat Roofing System**


Ref: (SDsB1-0611) Issue No: 7 - August 20

#### **TA-20**

The TA-20 system, part of the Langley Parafor range, is a premium quality, torch applied, high performance SBS elastomeric membrane warm roof system for flat or sloping roofs which carries a 20 year independently insured guarantee for materials, design, workmanship and consequential loss. The cap sheet is available in several colours for architectural purposes and delineating walkways etc.

#### When to Specify

This system is for new build or refurbishment projects (where conditions allow, existing systems can be overlaid, avoiding costly strip-ups). Suitable for all roof decks (timber boarding requires a nailed attachment layer in accordance with BS 8747:2007).



Example insulation depth shown above is typical.

 $<sup>^{\</sup>star}$  Additional insulation thicknesses are available or as a tapered (cut to falls) option.

TA-20 System			
	Layer	Thickness	Weight
1	Parafor 30 GS	4mm (3mm at selvedge)	4.6kg/m²
2	Adepar JS VV	2.2mm	2.7kg/m²
3	Parafoam Ultra	30 - 250mm (10mm increments)	3.84kg/m² (120mm)
4	Parevapo S VV	2.9mm	3.77kg/m²
Total System Weight: (based on 120mm insulation thickness) 14.91kg/m²			14.91kg/m²



## SA-20 Flame Free System

Ref: (SDsB6-0719) Issue No: 1 - July 19



#### **Durability**

- Extremely robust, yet flexible roof covering, 6.2mm thick (4mm cap sheet, 2.2mm underlay).
- Slip resistant granuale surface provides ample durability and punture resistance for maintenance foot traffic.
- Durable glass fibre reinforced vapour check provides a robust, watertight layer.



#### Resistance

- TA-20 membranes are covered by MOAT 31 (Reinforced Homogenous coverings of SBS Elastometric Bitumen).
- Parafor 30 GS achieves a 'resistance to damage' rating R4 (the highest level of acceptance) under MOAT 31.
- Fire Rating: Broof(t4) BS EN 13501-5:2016



### Life Span

• Long-term solution, life expectancy of at least 40 years.



# Certified and

- Parafor and Paradiene membranes are covered by a BBA Agrément Certificate.
- Original SBS elastromeric bitumen membrane system
- Products used in the UK and Europe since 1987
- In accordance with guidance outlined within NHBC technical requirements for flat roofs and balconies.



### Guarantee

- The system carries a 20 year independently insured guarantee for materials, design, workmanship and consequential loss.
- Installed by our national network of Langley Approved Contractors and installers, ensuring only the highest quality of installation is maintained.
- User friendly, quick and easy to install.
- A full range of accessories/supporting products are included under a single comprehensive guarantee, which includes: rooflights, refurbishment outlets, vents, leadfree flashings, edge trims etc.
- All Langley elastomeric membranes have been developed in accordance with the European Union of Agrément (UEAtc) and are manufactured and tested in accordance with UEAtc MOAT special directives (Methods of Assessment and Testing).



#### **Holistic Package**

For users peace of mind, this system is supported by the full Langley package that includes: surveys, condition reports and proposals, specifications, site monitoring and reporting, technical and design advice, guarantee inspections, all at no additional cost.