

## LangStik SF

Product Ref: (DsA6-0609)  
Issue No: 02-1114



### PU ADHESIVE

#### DESCRIPTION

**LangStik SF PU Adhesive** is a single component, cold applied, moisture-curing polyurethane adhesive.

#### USE

**LangStik SF PU Adhesive** has been formulated for bonding insulation boards and bituminous membranes to various substrates. It is compatible with the following insulation boards:

Polyurethane / Polyisocyanurate / Expanded Polystyrene / Extruded Polystyrene

#### CHARACTERISTICS

<b>Colour:</b>	Brown	<b>Base:</b>	Polyurethane
<b>Tack Life:</b>	20 minutes	<b>Cleaner:</b>	Solvent (White Spirit)
<b>Coverage:</b>	100 - 200 grms/m <sup>2</sup>	<b>Shelf Life:</b>	3 months @ 5 - 25°C

#### APPLICATION

**LangStik SF PU Adhesive** is applied direct from the can (pierce can to form a 20 mm hole) in a serpentine motion, forming 15 - 20 mm beads. Boards/membranes should be positioned within 10 - 15 minutes (depending on atmospheric conditions). Once applied, the adhesive will rapidly foam to form a durable bond.

#### PACKAGING

Container	: 6.5 kg / metal can
Labelling	: <b>LangStik SF PU Adhesive</b>

## LangStik SF

Product Ref: (DsA6-0609)  
Issue No: 02-1114

### STORAGE

LangStik SF PU Adhesive:

- Store in cool, well ventilated conditions.
- Keep container tightly closed.
- Is moisture sensitive and if left in contact with air it will eventually 'skin over'.
- If water enters the container it will react, giving off carbon dioxide. This may cause pressurisation of closed containers.

### SAFETY

Operators are recommended to wear protective overalls with elasticated cuffs and closed neck, safety goggles and gloves. Masks may be required in certain conditions.

Classified as none flammable.

This document is only a guide.

Langley Waterproofing Systems Ltd reserves the right to change the composition and fixing recommendations of products as a result of the evolution of knowledge and technology.