

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name: Pararapide Metal Primer
Type of Product: Liquid Primer

1.2. Supplier Details

Langley Waterproofing Systems Limited
Langley House,
Lamport Drive,
Heartlands Business Park,
Daventry,
Northants,
NN11 8YH
Phone: 01327704778
Fax: 01327704845
Email: enquiries@langley.co.uk
Web: www.langley.co.uk

2. SECTION 2: HAZARDS IDENTIFICATION

Hazard Statements

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

2.1. Classification

Hazard Statements

Flam. Liq. 2 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

Precautionary Statements

P240 Ground/bond container and receiving equipment.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking.
P280 Wear protective gloves/ eye protection.
P312 Call a POISON CENTRE/ doctor if you feel unwell.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P235 Store in a well-ventilated place. Keep cool.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008.
The product is classified and labelled according to the CLP regulation.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

Hazard pictograms



GHS02-Flame

Signal word - Danger.

2.3. Other Hazards

Results of PBT and vPvB assessment

PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Description:

Mixture of substances listed below with non-hazardous additions.

3.1. Dangerous components:

CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate H225; STOT SE 3, H336	10-<25%
------------------------------------	----------------------------------------	---------

Additional information: For the wording of the listed risk phrases refer to section 16.

4. SECTION 4: FIRST-AID MEASURES (ACTIONS)

4.1. Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Take affected persons out of danger area and lay down.

Contact a doctor immediately.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Take affected persons into fresh air and keep quiet.

Seek medical treatment.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

4.2. Most important symptoms and effects

Headache
Dizziness
Skin sensitization.

5. SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing agents:
CO₂, sand, extinguishing powder, foam.

For safety reasons unsuitable extinguishing agents:
Water with full jet.

5.2. Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO).
Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Protective equipment:
Wear fully protective suit.
Wear self-contained respiratory protective device.

Additional information:
Cool endangered receptacles with water spray.
Collect contaminated water separately. It must not enter the sewage system.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage in to water course or sewage system.
Dilute with plenty of water.

6.3. Methods and material for containment and cleaning up

Do not flush with water or aqueous cleansing agents.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

6.4. Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7. SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid heat.
Keep cool, polymerisation will occur if container is heated.
Protect closed containers against pressure rise from heating.
In excessive heat, keep containers cool with water.
Do not refill residue into storage receptacles.
Ensure good ventilation/exhaustion at the workplace, at least 7 air changes to prevent formation of aerosols

Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.
Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
Only use with explosion-proof equipment.
Protect against electrostatic charges.
Protect from heat.

7.2. Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Store in a cool location.

Information about storage in one common storage facility:

Store away from oxidising agents.
Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well-sealed receptacles.
Storage in a collecting room is required.
Store under lock and key and with access restricted to technical experts or their assistants only.
Max. Storage temperature 30 °C.
Keep container tightly sealed.
Protect from heat and direct sunlight.

7.3. Specific end use(s)

Building coating or sealing.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities:
No further data; see item 7.

8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:		
108-65-6 2-methoxy-1-methylethyl acetate (20-<25%)		
WEL (Great Britain)		Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm
MAK (Switzerland)		Short-term value: 275 mg/m ³ , 50 ppm Long-term value: 275 mg/m ³ , 50 ppm S SSc;
141-78-6 ethyl acetate (15-<20%)		
WEL (Great Britain)		Short-term value: 400 ppm Long-term value: 200 ppm
MAK (Switzerland)		Short-term value: 2800 mg/m ³ , 800 ppm Long-term value: 1400 mg/m ³ , 400 ppm S SSc;
112945-52-5 SYNTHETIC AMORPHOUS SILICA (0.1-≤2.%)		
TWA (Great Britain)		Short-term value: 6 mg/m ³ Long-term value: 2.4 mg/m ³
TWA (Switzerland)		Short-term value: 4 mg/m ³
DNELs		
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	DNEL (population)	1.67 mg/kg bw/day (Long-term - systemic effects)
Dermal	DNEL (worker)	153.5 mg/kg bw/day (Long-term - systemic effects)
Inhalative	DNEL (population)	33 mg/m ³ (Long-term - systemic effects)
	DNEL (worker)	275 mg/m ³ (Long-term - systemic effects)

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

141-78-6 ethyl acetate		
Oral	DNEL (population)	4.5 mg/kg bw/day (Long-term - systemic effects)
Dermal	DNEL	63 mg/kg bw/day (Long-term - systemic effects)
Inhalative	DNEL (population)	37 mg/m ³ (Long-term - systemic effects)
	DNEL (population)	734 mg/m ³ (Acute - local effects)
		734 mg/m ³ (Acute - systemic effects)
		367 mg/m ³ (Long-term - systemic effects)
		367 mg/m ³ (Long-term - local effects)
	DNEL (worker)	1468 mg/m ³ (Acute - local effects)
		1468 mg/m ³ (Acute - systemic effects)
		734 mg/m ³ (Long-term - systemic effects)
		734 mg/m ³ (Long-term - local effects)

PNECs		
108-65-6 2-methoxy-1-methylethyl acetate		
PNEC		0.0635 mg/l (seawater)
		0.635 mg/l (freshwater)
141-78-6 ethyl acetate		
PNEC		0.22 mg/kg (ground)
		0.34 mg/kg (sediment)
		0.26 mg/l (water)

Additional information: The lists valid during the making were used as basis.

8.2. Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Respiratory protection:

Ensure good ventilation.

The use of respiratory protective hood is recommended because time limitations apply without the correct use of PPE.

Protection of hands:

Preventive skin protection: The use of barrier creams is recommended.

Protective gloves:

Check condition of protective gloves prior to each use.

The glove material has to be impermeable and resistant to the product/substance/preparation.

In selecting the glove material consideration should be given to the penetration times, rates of diffusion and the degradation.

After gloves have been removed wash hands with an industrial hand cleaner.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

Material of gloves

The selection of the suitable gloves depends not only on the material, but also on further marks of quality and can vary from manufacturer to manufacturer.

As the product is a combination of several substances, the resistance of the glove material cannot be calculated in advance and will need to be checked prior to use.

Protective gloves according EN 374.

Penetration time of glove material

This recommendation is mainly on a one-time use as a short-term protection Liquid splashes. For other applications, you should contact a glove manufacturer.

The exact break through time has to be determined by the manufacturer of the protective gloves and has to be observed.

For permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable: Butyl rubber, BR.

For permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR.

Not suitable are gloves made of the following materials:

Leather gloves.

Eye protection:

Tightly sealed goggles.

EN-Standard: EN 166.

Body protection:

Protective work clothing.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General Information:

Appearance:

Form:

Fluid.

Colour:

According to product specification.

Odour:

Fruit-like.

Odour threshold:

Not determined.

PH-value at 20 °C:

Not determined.

Change in condition:

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

77 °C (Ethylacetat)

Flash point:

5 °C (DIN EN ISO 3680)

Flammability (solid, gaseous):

Not applicable.

Ignition temperature:

315 °C (1-Methoxy-2-propylacetat)

Self-igniting:

Product is not self-igniting.

Danger of explosion:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:

2.1 Vol % (Ethylacetat)

Upper:

11.5 Vol % (Ethylacetat)

Vapour pressure at 20 °C:

4.9 hPa (Ethylacetat)

Density at 20 °C:

1.51 g/cm³ (EN ISO 2811-1)

Evaporation rate:

Not determined.

Solubility in / Miscibility with water:

Fully miscible.

Partition coefficient (n-octanol/water):

Not determined.

Viscosity:

Dynamic at 20 °C:

2000 mPas (EN ISO 2555)

Solvent content:

Organic solvents:

36.4 %

VOC (EC)

36.39 %

Solids content:

64.0 %

10. SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

See Section 10.2.

10.2. Chemical Stability

Conditions to avoid: No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

Exothermic reaction.

Reacts with peroxides and other radical forming substances.

A hazardous polymerization may occur after the exhaustion of the inhibitor.

10.4. Conditions to avoid

Avoid heat. Avoid direct sunlight.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

10.5. Incompatible materials:

Violent reaction with peroxides and other reducing agents.

10.6. Hazardous decomposition products:

No dangerous decomposition products when used according to specifications.

Additional information:

Emergency procedures will vary depending on individual circumstances. A contingency plan should be in place.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

There were no toxicological effects found during the application.

11.2. Acute toxicity

LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Inhalative	LC50/4h	91.5 mg/l (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8500 mg/kg (rat)
Dermal	LC50	5.000 mg/kg (rat)
Inhalative	LC50/4h	35.7 mg/l (rat)
141-78-6 ethyl acetate		
Oral	LD50	4934 mg/kg (rabbit) (OECD 401)
Dermal	LC50	>18000 mg/kg (rat)
	LC50	> 18000 mg/kg (rabbit)
Inhalative	LC50/4h	56 mg/l (rat)

Primary irritant effect:

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Other information (about experimental toxicology): Due to the high vapour pressure a harmful concentration in the air can be quickly reached. At high concentrations narcotic effects can occur.

Subacute to chronic toxicity: not tested.

Repeated dose toxicity: no data available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction): not tested.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

12. SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Aquatic toxicity:

108-65-6 2-methoxy-1-methylethyl acetate	
EC50/48h	> 500 mg/l (daphnia magna)
LC50/96h	100 - 180 mg/l (Rainbow trout)

141-78-6 ethyl acetate	
EC50/24h	3090 mg/l (daphnia magna) (DIN 38412, Part 11)
EC50/48h	164 mg/l (daphnia magna) 3300 mg/l (scenedesmus subspicatus)
LC50/96h	230 mg/l (fish) 455 mg/l (pimephales promelas)
NOEC/21d	2.4 mg/l (daphnia magna)
NOEC/72h	>100 mg/l (Alge (Desmodesmus subspicatus)) (OECD 201)

12.2. Persistence and degradability

The product is easily biodegradable.

12.3. Bioaccumulative potential

No further relevant information available.

12.4. Mobility in soil

No further relevant information available.

12.5. Additional ecological information

BOD5-value: 0.14 g/g (MMA)

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
Danger to drinking water if even small quantities leak into the ground.

12.6. Results of PBT and vPvB assessment

PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Hazardous waste according to Waste Catalogue (EWC).

If recycling is not possible, waste must be in compliance with local regulations to be removed.

Recommendation

Uncured product residues are special waste.

Cured product residues are not hazardous waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste disposal key:

The following Waste Codes of the European Waste Catalogue (EWC), are considered a recommendation.

The disposal must be coordinated with the local waste disposal company.

Liquid product:

080111 * paint and varnish containing organic solvents or other dangerous substances.

080199 waste nec.

Cured product residues:

080112 paint and varnish wastes other than those mentioned in 080111.

080410 adhesive waste adhesives and sealants other than those mentioned in 080409.

European waste catalogue 080111 * (recommended).

Uncleaned packaging:

Recommendation:

This material and its container must be disposed of as hazardous waste.

Disposal must be made according to official regulations.

14. SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

ADR, IMDG, IATA: UN1263

14.2. UN proper shipping name

ADR: 1263 PAINT, special provision 640H

IMDG, IATA: PAINT

14.3. Transport hazard class

ADR, IMDG, IATA:



Class: 3 Flammable liquids.

Label: 3

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

14.4. Packing group

ADR, IMDG, IATA: III

14.5. Environmental hazards

Marine pollutant: No

14.6. Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler): 33

EMS Number: F-E,S-E

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

14.8. Transport/Additional information

ADR

Limited quantities (LQ): 5L

Excepted quantities (EQ): Code: E1
Maximum net quantity per inner packaging: 30 ml.
Maximum net quantity per outer packaging: 1000 ml.

Transport category: 3

Tunnel restriction code: D/E

Remarks: Classification according to viscosity clause (2.2.3.1.4).

IMDG

Limited quantities (LQ): 5L

Excepted quantities (EQ): Code: E1
Maximum net quantity per inner packaging: 30 ml.
Maximum net quantity per outer packaging: 1000 ml.

Remarks: Classification according to viscosity clause (2.3.2.3).

UN "Model Regulation": UN 1263 PAINT, SPECIAL PROVISION 640H, 3, III

15. SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions under the Maternity Protection Directive (94/33/EC).

Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

15.2. Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16. SECTION 16: OTHER INFORMATION

This information relates to the product as delivered.

Sector of Use:

Relevant identified uses of the mixture.

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites.

SU19 Building and construction work.

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen).

Uses advised against:

SU21 Consumer uses: Private households / general public / consumers.

Relevant phrases:

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Training hints:

Instruction must take place before the start of employment and at least annually thereafter.

Department issuing MSDS:

Division product safety.

Pararapide Metal Primer

Product Ref: (DsC40-0516)
Issue No: 01

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail).

ICAO: International Civil Aviation Organisation.

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road).

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

GHS: Globally Harmonised System of Classification and Labelling of Chemicals.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

VOC: Volatile Organic Compounds (USA, EU).

DNEL: Derived No-Effect Level (REACH).

PNEC: Predicted No-Effect Concentration (REACH).

LC50: Lethal concentration, 50 percent.

LD50: Lethal dose, 50 percent.

PBT: Persistent, Bioaccumulative and Toxic.

vPvB: very Persistent and very Bioaccumulative.

Flam. Liq. 2: Flammable liquids, Hazard Category 2.

Flam. Liq. 3: Flammable liquids, Hazard Category 3.

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2.

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2.

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1.

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3.

Asp. Tox. 1: Aspiration hazard, Hazard Category 1.

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2.

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3.

This document is only a guide.

Langley Waterproofing Systems Ltd reserves the right to change the composition and fixing recommendations of products as a result of the evolution of knowledge and technology.