

Pararapide Nosing

Product Ref: (DsL25-0616)
Issue No: 01



DESCRIPTION

Pararapide Nosing easily integrates with other the Pararapide systems offer outstanding slip resistance and mechanical protection for stair edges.

USE

Pararapide Nosing can be combined with Pararapide waterproofing and surfacing systems.

PACKAGING

Length:	2.00 m
Profile depth (top face):	41.0 mm
Profile height (front face):	23.2 mm

APPLICATION

If the entire area is to be waterproofed, the waterproofing system must already be installed before the edge protector can be bonded to the substrate.

Before the edge protector is fitted in place, the contact faces must be abraded mechanically and completely de-greased with Pararapide Cleaner.

Pararapide Filler is used to bond the edge protector to the step. Please refer to the relevant product information sheet. Use a small trowel to apply closely spaced spots of Pararapide Filler to the inside of the edge protector profile.

To achieve a flush interface with the edge profile, we recommend that you use Pararapide SL Mortar and Pararapide Sealer Coat as the final wearing layer.

Use masking tape to prevent contamination of the edge protector during subsequent operations.

STORAGE

Store lying flat in a dry area and protected against moisture.

Pararapide Nosing

Product Ref: (DsL25-0616)
Issue No: 01

SAFETY

Please refer to the Health and Safety data sheets for the products used.

This document is only a guide.

Langley Waterproofing Systems Ltd reserves the right to change the composition and fixing recommendations of products as a result of the evolution of knowledge and technology.