

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name: Pararapide Slip-Inhibiting Sealer Coat
Type of Product: Liquid Sealer

1.2. Supplier Details

Langley Waterproofing Systems Limited
Langley House,
Lamport Drive,
Heartlands Business Park,
Daventry,
Northants,
NN11 8YH
Phone: 01327704778
Fax: 01327704845
Email: enquiries@langley.co.uk
Web: www.langley.co.uk

2. SECTION 2: HAZARDS IDENTIFICATION

Hazard-determining components of labelling:

- Methyl methacrylate.
- 2-ethylhexyl acrylate.

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame
Flam. Liq. 3 H226 Flammable liquid and vapour



GHS07
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02-Flame



GHS07-Exclamation Mark

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

Signal word - Warning.

Hazard-determining components of labelling:

2-ethylhexyl acrylate methyl methacrylate

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/ eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P312 Call a doctor if you feel unwell.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other Hazards

Results of PBT and vPvB assessment

PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Description:

Mixture of substances listed below with non-hazardous additions.

3.1. Dangerous components:

CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453158-3	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	>10-<25%
CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-0000 01-2119452498-28-0025 01-2119452498-28-0028	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	>2.5-<10%

Additional information: For the wording of the listed risk phrases refer to section 16.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

4. SECTION 4: FIRST-AID MEASURES (ACTIONS)

4.1. Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.
Take affected persons out of danger area and lay down.
Contact a doctor immediately.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.
Take affected persons into fresh air and keep quiet.
Seek medical treatment.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

4.2. Most important symptoms and effects

Headache
Dizziness
Skin sensitization.
Irritant to skin, eyes and respiratory system.

4.3. Indication of any immediate medical attention and special treatment needed

After inhalation, even in the absence of signs of disease, give inhaled corticosteroid (eg Ventolair).

5. SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing agents:

CO₂, sand, extinguishing powder, foam.

For safety reasons unsuitable extinguishing agents:

Water with full jet.

5.2. Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO).
Nitrogen oxides (NOx).
Steams are more difficult than air.
Creeping steams can lead to the inflammation in a larger distance.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

5.3. Advice for firefighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Additional information:

Cool endangered receptacles with water spray.

Collect contaminated water separately. It must not enter the sewage system.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures



Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

6.2. Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage in to water course or sewage system.

6.3. Methods and material for containment and cleaning up

Do not flush with water or aqueous cleansing agents.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4. Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Cool down container when heated. Cool containers exposed to heat with water. Emergency cooling must be provided in the event of an ambient fire. Keep container tightly closed to prevent heat build up (pressure increase). Avoid heat.

Not giving remnants back into the storage vessels.

Providing good ventilating/suction at work at least 7-fold air changes per hour.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Only use with explosion-proof equipment.

Protect against electrostatic charges. Protect from heat.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

7.2. Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Store in a cool location.

Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well-sealed receptacles.

Storage in a collecting room is required.

Store under lock and key and with access restricted to technical experts or their assistants only.

Max. Storage temperature 30 °C.

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3. Specific end use(s)

Building coating or sealing.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:		
80-62-6 methyl methacrylate (2.5-<10%)		
WEL (Great Britain)		Short-term value: 416 mg/m ³ , 100ppm Long-term value: 208 mg/m ³ , 50 ppm
103-11-7 2-ethylhexyl acrylate (10-<20%)		
MAK (Switzerland)		Short-term value: 38 mg/m ³ , 5 ppm Long-term value: 38 mg/m ³ , 5 ppm S SSc;
DNELs		
80-62-6 methyl methacrylate		
Inhalative	DNEL (population)	74.3 mg/m ³ (Long-term - systemic effects) 105 mg/m ³ (Long-term - local effects)
	DNEL (worker)	210 mg/m ³ (Long-term - local effects) 210 mg/m ³ (Long-term - systemic effects) Long-term
103-11-7 2-ethylhexyl acrylate		
Dermal	DNEL	242 µg/cm ² (Employee / Industrial / Commercial) Long-term and short-term
Inhalative	DNEL	37.5 mg/m ³ (Employee / Industrial / Commercial) (Langzeit)

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

PNECs		
80-62-6 methyl methacrylate		
PNEC		< 0.94 mg/l (water)
PNEC sediment		1.47 mg/kg dw (ground) 5.74 mg/kg dw (freshwater)
103-11-7 2-ethylhexyl acrylate		
Boden		2.3 mg/l (Soil microorganisms) 1 mg/l (ground)
PNEC		0.0023 mg/kg (oral intake)
Water		0.126 mg/l (sediment) 0.002727 mg/l (freshwater)

8.2. Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

Respiratory protection:

Ensure good ventilation.

In interiors and at transgression of the limiting values breath filtration device: Filter type A1 using an air recycling independent breathing apparatus at high concentrations A2 at an intensive or longer outline.



Protection of hands:

Protective gloves:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Preventive skin protection by use of skin-protecting agents is recommended. After use of gloves apply skin-cleaning agents and skin cosmetics.

Check protective gloves prior to each use for their proper condition.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Material of gloves

The selection of the suitable gloves depends not only on the material, but also on further marks of quality and can vary from manufacturer to manufacturer. As the product is a combination of several substances, the resistance of the glove material cannot be calculated in advance and will need to be checked prior to use.

Protective gloves according EN 374.

Suitable material: nitrile.

Penetration time of glove material

This recommendation is mainly on a one-time use as a short-term protection against liquid splashes. For other applications, you should contact a glove manufacturer.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

The exact break through time has to be found out by the manufacturer of the protective gloves and must be observed.

For permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable: Butyl rubber, BR.

For permanent contact gloves made of the following materials are suitable:
Butyl rubber, BR.

Not suitable are gloves made of the following materials:
Leather gloves.

Eye protection:



Tightly sealed goggles.
EN-Standard: EN 166.

Body protection:



Protective work clothing.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General Information:

Appearance:

Form:

Fluid.

Colour:

Various colours.

Odour:

Ester-like.

Odour threshold:

Not determined.

PH-value:

Not determinable.

Change in condition:

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

101 °C (MMA)

Flash point:

23 °C (DIN EN ISO 3680).

Flammability (solid, gas):

Not applicable.

Ignition temperature:

252 °C (2-EHA)

Self-igniting:

Product is not self-igniting.

Danger of explosion:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:

1.7 Vol % (MMA)

Upper:

12.5 Vol % (MMA)

Vapour pressure at 20 °C:

0.2 hPa (MMA)

Density at 20 °C:

1.8 g/cm³ (EN ISO 2811-1))

Evaporation rate:

Not determined.

Solubility in / Miscibility with water:

Not miscible or difficult to mix.

Partition coefficient (n-octanol/water):

log Pow: 4.29 (2-EHA); (25 °C, OCED 107)

Log Pow: 1.38 (MMA)

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

Viscosity:	
Dynamic at 20 °C:	4,300 mPas (EN ISO 2555).
Solvent content:	
Organic solvents:	0.1 %
VOC (EC)	0.11 %
Solids content:	79.1 %

10. SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

See Section 10.2.

10.2. Chemical Stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3. Possibility of hazardous reactions

Exothermic reaction.

Reacts with peroxides and other radical forming substances.

A hazardous polymerization may occur after the exhaustion of the inhibitor.

10.4. Conditions to avoid

Avoid heat. Avoid direct sunlight.

10.5. Incompatible materials:

Reactions with peroxides and other free-radical generators.

10.6. Hazardous decomposition products:

No dangerous decomposition products used according to specifications.

Additional information:

Emergency procedures will vary depending on individual circumstances. A contingency plan should be in place.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

There were no toxicological effects found during the application.

11.2. Acute toxicity

Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
80-62-6 methyl methacrylate		
Inhalative	LC50/4h	259 mg/l (rat)
80-62-6 methyl methacrylate		
Oral	LD50	> 5000 mg/kg (rat) (OECD 401)
	NOAEL	2000 ppm (rat) n drinking water, 6-2000 ppm Findings: No toxic effects
Dermal	LC50	> 5000 mg/kg (rabbit)
Inhalative	NOAEL	25 ppm (rat) 25 - 400 ppm Findings: Damage to mucous membranes in the nose at 400 ppm
	LC50/4h	29.8 mg/l (rat)
103-11-7 2-ethylhexyl acrylate		
Oral	LD50	4435 mg/kg (rat) (BASF-Test)
Dermal	LC50	7520 mg/kg (hare)

Primary irritant effect:

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation: May cause an allergic skin reaction.

Other information (about experimental toxicology): Due to the high vapour pressure a harmful concentration in the air can be quickly reached. At high concentrations narcotic effects can occur.

Subacute to chronic toxicity: not tested.

Toxicokinetics, metabolism and distribution: The drug is metabolized rapidly (MMA).

Repeated dose toxicity: no data available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction): not tested.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause respiratory irritation.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

12. SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

80-62-6 methyl methacrylate	
EC3/16h	100 mg/l (<i>Pseudomonas putida</i>) (Zellvermehrung, Wachstumstest, Bringmann-Kühn)

Aquatic toxicity:

80-62-6 methyl methacrylate	
EC50/48h	69 mg/l (<i>daphnia magna</i>) (OECD 202)
EC50/72h	> 110 mg/l (<i>Selenastrum capricornutum</i>) (OECD 201)
ErC50/72h	> 110 mg/l (<i>Pseudokirchneriella subcapitata</i>) (OECD 201)
LC50/96h	> 79 mg/l (Rainbow trout) (OECD 203)
NOEC	9.4 mg/l (<i>Danio rerio</i>) (OECD 210) fish early life stage test, 35 days
	37 mg/l (<i>daphnia magna</i>) (OECD 211) 21 days
NOEC/72h	> 110 mg/l (<i>Selenastrum capricornutum</i>) (OECD 201)

103-11-7 2-ethylhexyl acrylate	
other (28d)	> 1000 mg/kg (Soil microorganisms) (OECD 217) The product has not been tested. The statement has been derived from products of a similar structure or composition.
EC50/48h (static)	1.3mg/l (<i>daphnia magna</i>) (OECD 202, Part 1)
NOEC/21d	0.19 mg/l (<i>daphnia magna</i>) The details of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from products of a similar structure or composition.
LC50/96h (static)	1.81 mg/l (Rainbow trout) (OECD 203)
EC50/72h (static)	1.71 mg/l (<i>scenedesmus subspicatus</i>) (OECD 201) The details of the toxic impact relates to the analytically determined concentration.

12.2. Persistence and degradability

The product is easily biodegradable.

12.3. Bioaccumulative potential

2-EHA:

Can be accumulated in organisms.

Bioaccumulation potential:

Bioconcentration Factor: 282.4 (calculated)

12.4. Mobility in soil

MMA: A binding to the solid phase of soil, sediment and sewage sludge is not expected. From the water surface the substance is slowly evaporated into the atmosphere. If the substance is released into the environment it will remain within the location into which it was released.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

2-EHA: The product floats on water and does not dissolve. Adsorption on soil is not likely.

12.5. Additional ecological information

COD-value: 2-EHA: Theoretical oxygen demand (TOD) = 5.6 g/g

BOD5-value: 0.14 g/g (MMA)

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

12.6. Results of PBT and vPvB assessment

PBT: Does not meet the PBT-criteria of Annex XIII of REACH (self assessment).

vPvB: Does not meet the vPvB-criteria of Annex XIII of REACH (self assessment).

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Hazardous waste according to Waste Catalogue (EWC).

If recycling is not possible, waste must be in compliance with local regulations to be removed.

Recommendation

Uncured product residues are special waste.

Cured product residues are not hazardous waste.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste disposal key:

The following Waste Codes of the European Waste Catalogue (EWC), are considered a recommendation.

The disposal must be coordinated with the local waste disposal company.

Liquid product:

080111 * paint and varnish containing organic solvents or other dangerous substances.

080199 waste nec.

Cured product residues:

080112 paint and varnish wastes other than those mentioned in 080111.

080410 adhesive waste adhesives and sealants other than those mentioned in 080409.

European waste catalogue 080111 * (recommended).

Uncleaned packaging:

Recommendation:

This material and its container must be disposed of as hazardous waste.

Disposal must be made according to official regulations.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

14. SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

ADR, ADN, IMDG: Void

IATA: UN1263

14.2. UN proper shipping name

ADR, ADN, IMDG: Void

IATA: PAINT

14.3. Transport hazard class

ADR, ADN, IMDG:

Class: Void

IATA:



Class: 3 Flammable liquids.

Label: 3

14.4. Packing group

ADR, IMDG: Void

IATA: III

14.5. Environmental hazards

Marine pollutant: No

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

14.8. Transport/Additional information

ADR

Remarks: Classification according to viscosity clause (2.2.3.1.5)
> 450 l: 3 F1, III

IMDG

Remarks: Classification according to viscosity clause (2.3.2.5)
> 30 l: 3, III

UN "Model Regulation": Void

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

15. SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I: None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Information about limitation of use:

Employment restrictions under the Maternity Protection Directive (94/33/EC).

Employment restrictions for maternity Directive (92/85/EEC) for expectant and nursing mothers.

15.2. Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16. SECTION 16: OTHER INFORMATION

This information relates to the product as delivered.

Sector of Use:

Relevant identified uses of the mixture.

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites.

SU19 Building and construction work.

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen).

Uses advised against:

SU21 Consumer uses: Private households / general public / consumers.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Training hints:

Instruction must take place before the start of employment and at least annually thereafter.

Pararapide Slip-Inhibiting Sealer Coat

Product Ref: (HSDSPR22-0221)
Issue No: 01

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail).

ICAO: International Civil Aviation Organisation.

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road).

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

GHS: Globally Harmonised System of Classification and Labelling of Chemicals.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

VOC: Volatile Organic Compounds (USA, EU).

DNEL: Derived No-Effect Level (REACH).

PNEC: Predicted No-Effect Concentration (REACH).

LC50: Lethal concentration, 50 percent.

LD50: Lethal dose, 50 percent.

PBT: Persistent, Bioaccumulative and Toxic.

vPvB: very Persistent and very Bioaccumulative.

Flam. Liq. 2: Flammable liquids, Hazard Category 2.

Flam. Liq. 3: Flammable liquids, Hazard Category 3.

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2.

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2.

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1.

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3.

Asp. Tox. 1: Aspiration hazard, Hazard Category 1.

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2.

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3.

This document is only a guide.

Langley Waterproofing Systems Ltd reserves the right to change the composition and fixing recommendations of products as a result of the evolution of knowledge and technology.