

Pararapide SL Mortar Resin

Product Ref: (DsL29-0516)
Issue No: 02-0117



DESCRIPTION

Pararapide SL Mortar Resin is a fast-curing, flexibilised, PMMA-based resin specifically designed for the requirements of Pararapide SL Mortar. It gives good application properties, including application at sub-zero temperatures and flexibility to Pararapide SL Mortar.

USE

Pararapide SL Mortar Resin is the base resin for Pararapide SL Mortar. It acts as binder in these products.

PACKAGING

Pararapide SL Mortar Resin is one of 3 components supplied together; **Pararapide SL Mortar Resin** (base resin), **Pararapide SL Mortar Sand** (powder component) and **Pararapide catalyst**.

| Summer | | Winter | |
|---------|--|---------|--|
| 10.00kg | Pararapide SL Mortar Resin (base resin) | 10.00kg | Pararapide SL Mortar Resin (base resin) |
| 23.00kg | Pararapide SL Mortar Sand (powder component) | 23.00kg | Pararapide SL Mortar Sand (powder component) |
| 0.20kg | Pararapide Catalyst (2x0.1kg) | 0.40kg | Pararapide Catalyst (4x0.1kg) |
| 33.20kg | | 33.40kg | |

APPLICATION

Consumption Rate: 4kg/m²

For application information please see the SL Mortar Product Data Sheet (DsL24-0516).

TYPICAL PROPERTIES

Density: 1.00 g/cm³

Pararapide SL Mortar Resin

Product Ref: (DsL29-0516)
Issue No: 02-0117

STORAGE

Store products sealed in their original airtight container and in a cool, dry and frost free place.

Unopened products have a shelf life of at least 6 months. Direct sunlight on the containers should be avoided, including on site.

After removing some of the contents, reseal the containers so they are airtight.

SAFETY

Please refer to the Health and Safety data sheets for the products used.

This document is only a guide.

Langley Waterproofing Systems Ltd reserves the right to change the composition and fixing recommendations of products as a result of the evolution of knowledge and technology.